



ALUMINIUM OXIDE

BLAST & PEEN SERVICES PTE LTD
11 Tuas South Link 1
#03-18 SHINE@TUAS SOUTH | Singapore 636901

Office Phone
+65 8811 1883

Handphone
+65 9850 0121

Email Address
sales@bnp.com.sg

Website
www.bnp.com.sg



i DESCRIPTION

Fused Aluminium Oxide is an artificial corundum, produced to form a very hard angular abrasive. Aluminium Oxide is used for cleaning, descaling, etching, deburring, finishing, coating removal and surface preparation.


Aluminium Oxide produces an etched finish; finer grits produce a dull matt finish, while larger grits produce a deep rough etch. Aluminium Oxide is an aggressive blasting media with a very fast cutting speed. Available in brown and white.

+ APPLICATION

Cleaning, descaling, coating and contamination removal, etching and surface preparation of ferrous and non ferrous metallic parts prior to rework, painting, coating, anodizing and powder coating.

Removal of thermal metal spray and carbon deposits from jet and gas engine components and turbochargers prior to rebuild, anodizing and thermal metal spray.

Decorative glass, stone, metal and wood etching and carving.



Size in Details

Grit no.	12	16	24	36	46	60	80
Mean size in μm	1680	1190	710	500	355	250	180

Grit no.	100	120	150	180	220	240	320
Mean size in μm	125	105	75	63	53	45	30

Note. Standard product sizing is per FEPA 42-GB-1984. Other sizes and specifications available upon request.

Physical Properties

Hardness	Specific Gravity	Bulk Density	Shape	Colour
9.0 Mohs	> 3.9 g/cm ³	≈1800kg/m ³	Angular	Dark brown

Typical Chemical Composition - Brown

Al ₂ O ₃	TiO ₂	SiO ₂	Fe ₂ O ₃	CaO
95.52%	3.05%	0.72%	0.16%	0.022%

Typical Chemical Composition - White

Al ₂ O ₃	Na ₂ O	SiO ₂	Fe ₂ O ₃	CaO
99.33%	0.34%	0.036%	0.09%	0.05%