



SILICON CARBIDE

BLAST & PEEN SERVICES PTE LTD

11 Tuas South Link 1

#03-18 SHINE@TUAS SOUTH | Singapore 636901

Office Phone
+65 8811 1883

Handphone
+65 9850 0121

Email Address
sales@bnp.com.sg

Website
www.bnp.com.sg



DESCRIPTION

Silicon Carbide is an aggressive sharp angular abrasive, and is the hardest blasting abrasive available. Silicon Carbide particles fracture in use to produce new sharp cutting edges. The hardness of the material greatly reduces blasting cycle times.

Silicon Carbide produces an etched finish; finer grits produce a dull matt finish, while larger grits produce a deep rough etch. Silicon Carbide is an aggressive blasting media with a very fast cutting speed.

APPLICATION

Cleaning, descaling, coating and contamination removal, etching and surface preparation of ferrous and non ferrous metallic parts prior to rework, painting, coating, anodizing and powder coating.

Removal of thermal metal spray and carbon deposits from jet and gas engine components and turbochargers prior to rebuild, anodizing and thermal metal spray.

Decorative glass, stone, metal and wood etching and carving.



Size in Details

Grit no.	8	12	16	24	36	46	60
Mean size in μm	2380	1680	1190	710	500	355	250

Grit no.	80	100	120	150	180	220	240
Mean size in μm	180	125	105	75	63	53	45

Note: Standard product sizing is per FEPA 42-GB-1984. Other sizes and specifications available upon request.

Physical Properties

Hardness	Specific Gravity	Bulk Density	Shape	Colour
> 9.0 Mohs	> 3.2 g/cm ³	≈1800kg/m ³	Angular	Black

Typical Chemical Composition

SiC	SiO ₂	Si	Fe	Al	C
97.8%	0.6%	0.8%	0.23%	0.3%	0.3%